



SAFETY DATA SHEET

TYRE DRESSING

Page 1

Issued: 06/07/02

Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: TYRE DRESSING

Product code: JU 139

Use / description of product: Flammable. Irritant. Liquid.

Company name: JEWELULTRA LTD

Downs Court

Yalding Hill

Maidstone

Kent

ME18 6AL

Tel: 01622 815679

2. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients: STRAIGHT RUN Kerosine - Solvent Naphtha (Petroleum), Medium Aliph. >60%

CAS: 64742-88-7

EINECS: 265-191-7

[Xn] R65; [Xi] R38; [N] R51/53;

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Irritating to skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: Nausea and stomach pain may occur. There may be vomiting. Inhalation of fumes from the stomach may cause symptoms similar to direct inhalation.

Inhalation: Nausea and stomach pain may occur. There may be vomiting. Drowsiness or mental confusion may occur. There may be loss of consciousness.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Do not induce vomiting. If conscious, give 1 pint of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. If conscious, ensure the casualty sits or lies down. If

[cont...]

SAFETY DATA SHEET

TYRE DRESSING

breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Water spray. Alcohol or polymer foam. Dry chemical powder. Use water spray to cool containers.

Exposure hazards: In combustion emits toxic fumes.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Wash the spillage site with large amounts of water.

7. HANDLING AND STORAGE

Handling requirements: Ensure there is sufficient ventilation of the area. Avoid direct contact with the substance.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Self-contained breathing apparatus must be used in handling.

Hand protection: Protective gloves.

Eye protection: Safety goggles. Ensure eye bath is to hand.

Skin protection: Protective clothing with elasticated cuffs and closed neck. Boots made of PVC.

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Moderate

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Oily

Flash point°C: 35

Relative density: 0.83

10. STABILITY AND REACTIVITY**Stability:** Stable under normal conditions.**Conditions to avoid:** Sources of ignition.**Materials to avoid:** Oxidising agents.**Haz. decomp. products:** In combustion emits toxic fumes.**11. TOXICOLOGICAL INFORMATION****Chronic toxicity:** May cause sensitisation by skin contact.**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.**12. ECOLOGICAL INFORMATION****Mobility:** Insoluble in water. Readily absorbed into soil.**Persistence and degradability:** Slowly biodegradable**Bioaccumulative potential:** No data available.**Other adverse effects:** Toxic to aquatic organisms.**13. DISPOSAL CONSIDERATIONS****Disposal operations:** Via an authorised waste disposal contractor to an approved waste disposal site.

R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.**14. TRANSPORT INFORMATION****ADR / RID****UN no:** 1993**ADR Class:** 3**Hazard ID no:** 33**Labelling:** 3**IMDG / IMO****UN no:** 1993**Class:** 3.3**Packing group:** III**EmS:** 3-07**Marine pollutant:** YES**Labelling:** 3 FLAMMABLE LIQUID**IATA / ICAO****UN no:** 1993**Class:** 3**Packing group:** III**Packing instructions:** 310**Quantity:** 220 L**Labelling:** 3 FLAMMABLE LIQUID**15. REGULATORY INFORMATION****Hazard symbols:** Irritant.

Dangerous for the environment.



SAFETY DATA SHEET

TYRE DRESSING

Risk phrases: R10: Flammable.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety phrases: S2: Keep out of the reach of children.
S16: Keep away from sources of ignition - No smoking.
S23: Do not breathe ...
S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.
S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Risk phrases used in s.2: R65: Harmful: may cause lung damage if swallowed.
R38: Irritating to skin.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.